Our Products



Extruded particle board core faced with 1/8 HDF

PRODUCT INFORMATION

ADVANTAGES

- This unique material has design principles that give a high strength to weight ratio with the advantages of great impact resistance and low thickness swelling
- Easily apply face materials (veneer, laminate, and coatings)
- Finish with a variety of edge options
- Rigid face material supports selected methods of attachment
- Optional skin thicknesses are available






SIZES AVAILABLE

- 1 3/8" x 48 x 96
- 1 ³/₄" x 48 x 96
- 2 1/4" x 48 x 96





• 1 %" x 48 x 96

• 2" x 48 x 96





PRODUCT SPECIFICATION

TECHNICAL DATA

	MATERIAL THICKNESS					
	1 3/8"	1 5/8"	1 3/4"	2"	2 1/4"	
SKIN THICKNESS	0.118"	0.240"	0.118"	0.240"	0.375"	
CORE THICKNESS	1.120"	1.120"	1.500"	1.500"	1.500"	
MAX SCREW WITHDRAWN FORCE, LBF	137	-	138	-	-	
MAX SCREW TENSILE FORCE, LBF	138	-	379	-	-	
MAX TENSILE STRENGTH, PSI	49	-	97	-	-	
COMP, STRENGTH @5% STRAIN, PSI	236	-	324	-	-	
MAX FLEXURE FORCE, LBF	218	-	270	-	-	
MODULUS OF RUPTURE, PSI	1740	-	1740	-	-	
MODULUS OF ELASTICITY, PSI	193483	-	19143	-	-	
WEIGHT PER PANEL, LB** (48 X 96)	116	138	125	147	181	

PACKAGING QUANTITY PER SKID

	MATERIAL THICKNESS						
SHEET SIZE	1 3/8"	1 5/8"	1 3/4"	2"	2 1/4"		
48 X 96	34	30	27	24	20		

^{*} Testing conducted with Varianta Screw HC 013.30.900

^{**} Actual measured length may vary due to temperature and humidity. Weight provided is for comparative analysis only.